



Fort Valley Utility Commission
PO Box 1529
Fort Valley Ga 31030-1529
Project# 4601-2122-02

Please submit a proposal for the following equipment as described below.

Proposals should be received by Fort Valley Utility Commission Offices **before 2:00 P.M., local time, on Tuesday, December, 21st, 2021**, to the attention of Alvin Wallace, Purchasing Agent PO Box 1529 Fort Valley, Ga, 31030. Proposals will be opened on December 22nd at 9:30 AM and evaluated on the basis of product, price, delivery, and completeness / neatness of the bid. Please include complete Derrick and Chassis specifications in bid packet. Units bid must have a guaranteed delivery date no later than September 20, 2023.

Item 1: One New Digger Derrick Stock Unit with the Options Shown Below as a Minimum. Proposals should include a complete listing of lifting capacities. 30,000 lbs. Maximum lifting capacity preferred. Supplier's quotation sheet specifies drivetrain and body type.

- Flatbed with bins behind cab with Rear Mount Derrick Over Rear Axle
- 47-Foot Full Pressure Hydraulic Derrick
- Turntable Winch
- Normal Winch Speed (15,000 lbs.)
- Two Speed Mechanical Shift Digger, 12,000 lbs., includes all of the components necessary to operate digger.
- Single Handle Controller, Full View Operator's Seat, One T-Handle 3 Function Controller and
- Foot Throttle, LED operator control lights.
- Standard Poles Guides for 18.00-inch Diameter Pole (Maximum).
- Rectangular externally wound filament fiberglass 3rd stage provides rigidity and strength.
- Large nut retention system for 2 ½" main hinge pin.
- A-Frame Outriggers with Folding Shoe
- Derrick Tong Protectors
- Dirt Auger, 18" Diameter with 2.5-inch Hex by 104-inch Long
- Winch Rope for Turntable Winch
- Load Line Swivel Hook, 8.5 Ton (Crosby)
- Hot Shift PTO for Automatic Transmission
- Spring Loaded Hoses Reel, 50 Foot Capacity
- Tool Circuit for Hose Reel
- 50' Conductive Hose Kit, Includes Quick Disconnects and Dust Caps
- 60" Pole Tamp with Quick Disconnects and Dust Caps
- Steel Body Finished in White.
- Stainless Steel Rotary Paddle Latches with Keyed Locks
- All Locks Keyed Alike
- Gas Shock (Gas Spring) Rigid Door Holders on all Vertical Doors

Fort Valley Utility Commission
PO Box 1529
Fort Valley Ga 31030-1529
Project# 4601-2122-02

- Minimum of one Chock Holder on Each Side of the Body with Retaining Lip in the Fender Panel
- Cone holder bracket fold down - post style with base on front to fold down away from chassis hood
- Front pole carrier kit bunk style with a ratchet with 2" wide webbing tie down strap to secure pole and pole bunk arm weldment.
- 1 Rear pole carrier assembly 20-24" bunk style, removable and bed mount.
- T-125 Style Pintle Hitch
- Set of Eye Bolts for Trailer Safety Chain. One Installed on each side of the Pintle Hitch.
- Operator Seat Access Step
- Lower Boom Rest Weldment
- Wood Outrigger Pads with Rope Handle (24" x 24" x 2.5")
- Mud Flaps
- Dock Bumpers (pair), Fixed Mounting, Installed at Rear
- Slope Indicator Assembly
- Triangular Reflector Kit
- Two 10 lbs. Fire Extinguishers with Light Duty Bracket
- 4-Corner Strobe Lighting
- Strobe Beacon
- Lights and Reflectors in accordance with FMVSS #108 Lighting Package.
- Dual Tone Back-Up with Outrigger Motion Alarm
- Standard Multi Point Grounding System
- Spring Loaded Grounding Reel
- 7-Way Trailer Receptacle (Pin Type) Installed at Rear
- Electric Trailer Brake Controller
- Non-Skid Coating Applied to all Walking Surfaces
- Vehicle Height Placard – Installed in Cab
- Dielectric Test Unit According to ANSI Requirements
- Stability Test Unit According to ANSI Requirements
- DOT Certification Required
- Regular Cab Drivetrain
- Minimum 300 HP Engine Rating
- Automatic Transmission
- GVWR 33,000 lbs.
- Air Brakes
- Parking Brake in Rear Wheels
- Horizontal Exhaust (Under Cab)
- 50 Gallon Fuel Tank
- Chassis without Frame Extensions
- Vinyl Split Bench Seat
- Front Bumper Mounted Hydraulic Winch 20,000-lb rated capacity